

Anchor Installation



To begin the installation process, place the Drive Cap* in the opening of the anchor.



Using a power driver or sledge hammer, drive the anchor into the ground.



When the anchor is flush with the ground, or no more than two (2") inches above the ground, remove the Drive Cap*.



Place the NEX® Tube into the anchor approximately six (6") inches.



Insert the NEX® Wedge™ between the anchor and the NEX® mailbox support. Use a hammer to secure it until it is well seated.



You have successfully and easily installed the next generation of sign post - NEX®.

NEX® Wedge™ Removal



The NEX® Wedge™ can easily be removed by using a Slide Hammer*. Simply place the hook of the Slide Hammer* in the slot of the Wedge and hammer upwards.



Once the Wedge is loosened, remove the Wedge and lift the NEX® Post out of the Anchor. Your NEX® Sign Post is removed with little effort and time. Without the Slide Hammer* it is virtually impossible to remove - making it tamper resistant.



Drive Cap*



Slide Hammer*

*suggested, but not required. Sold separately

NEX®

Manufacturer of NEX® Sign & Mailbox Support Products

*NEX® is protected by Canadian Patent #'s 2,369,517; 2,310,486 of S-Square Tube Products, Inc.

2275 W. Midway Blvd., Unit C
Broomfield CO · 80020

Tel. 303.286.7051 · www.s-squartube.com

